



SPX 1040



8800 lbs



15'1" - 47'7"



15'9" - 24'7"

	12320 lbs	1430 lbs	2T-D7: 88 lbs	JIB500G: 682 lbs	
	17'5"x4'7"x6'6"		1.24 MPH		25°
	9900 lbs		8.39 PSI		
	<p>Engine: 3 cylinders water cooled diesel, ISUZU mod. 3CB1, 2 rpm levels, EPA TIER 4 Motore: 3 cilindri diesel raffreddato a liquido, ISUZU mod. 3CB1, 2 livelli di regime, EPA TIER 4 Motor: Wassergekühlter 3 Zylinder Diesel Motor, ISUZU mod. 3CB1, 2 rpm, EPA TIER 4 Motor: Diesel 3 cilindros con refrigeración por aire, ISUZU mod. 3CB1, 2 niveles rpm, EPA TIER 4 Moteur: Diesel 3 cylindres, refroidissement à eau, ISUZU mod. 3CB1, accélérateur à 2 niveaux, EPA TIER 4</p>				
	8kW 240V-60Hz-AC 1F		110 lbs		
<p>Telescopic Boom: 1 base and 3 telescopic sections high-tensile structural steel. All sections synchronized and full power. Braccio Telescopico: 1 braccio principale e 3 telescopici in acciaio strutturale ad alta resistenza. Sfilo completamente idraulico e sincronizzato. Teleskopausleger: 1 Hauptausleger + 3 Hochwiderstand Stahl Teleskopausleger. Voll hydraulischer und teleskopierbarer Ausleger. Pluma Telescópica: 1 pluma principal y 3 telescópicas en acero de alta resistencia. Elementos sincronizados e hidráulicos. Flèche Téléscofique: 1 flèche principale et 3 téléscofiques en acier à haute résistance. Éléments synchronisés et hydrauliques.</p>					
	360° 1 rpm		-4°/80° 35°		
	15'1" - 47'7" 40"		1980 lbs - 262' - Ø 3/8 in 98/180 ft/min.		

